

## Tukwila Loader Ticket

Tukwila Loader Ticket - Loaders have been built to be able to function just about anywhere. They provide optimal traction and maneuverability due to a heavy-duty oscillating joint which offers 45-degree turning angles to the left and right, with 10 degrees of oscillation in both directions. Access is fixed to confined and tight spaces by narrow engine widths. Nearly all skid-steer loaders with equivalent operating capacities are unable to compete. The tires and bucket on the Gehl machine follow a steady turn radius also. This means the back tires of the loader follow the course of the front tires.

The articulated loaders features hydraulic precision and power that come together with all Gehl equipment. Lift arm and bucket float features allow these equipment to be able to perform light scraping and rearward leveling actions. Flat-face couplers, together with the two easily reachable auxiliary hydraulic lines power many tools and make changing the accessories an easy job to complete.

Gehl articulated loaders have distinctively built lift arms which are constructed to be able to achieve fast cycle times, great visibility and maximum strength. The specific linkage pattern makes it possible for for mechanical self-leveling action in both the downward and upward directions. It can also easily perform exceptional bucket dump angles at the top and mid ranges of the lift path along with providing excellent forward reach. Models 140 and 340 have parallel type linkage and the 540 model has "Z" bar type linkage. These linkage patterns provide great bucket breakout forces from two thousand four hundred thirty three pounds on the model 140 to 10,749lbs on the model 540.

Known all over the world for their ease of operation, Gehl articulated loaders provide excellent visibility and supreme ergonomics. The models 340 and 540 have closed cabs options offered. This provides comfort and safety for the operator. Secure operation and 360 degree visibility is sustained by positioning the one operating it above the load to guarantee an exceptional viewpoint of the accessory. An inching pedal permits the individual operating it to alter ground speed whilst maintaining a fixed engine speed. This feature enables the operator to optimally run attachments while ensuring precise machine velocity control. A multi-function joystick controls the travel direction, float, differential lock and auxiliary hydraulic functions, bucket as well as the lift arm.